



REV	MODIFICATION	DATE	DRAW
A0	Release To MA20130314	2013.03.15	Seven
A1	Release To ECN20150507	2015.05.11	Michelle

Specification

- Current Rating: 0.5A
- Voltage Rating: 40V AC
- Contact Resistance: 30mΩ Max.(Pin) 50mΩ Max.(Shell)
- Insulation Resistance: 100MΩ Min. At DC 500V
- Dielectric Withstanding Voltage: AC500V/Minute
- Operating Temperature: -25°C~+85°C

Material:

- Housing: High Temp. Thermoplastic UL94V-0
- Contact Pin: Copper Alloy T=0.15mm
- Shell: Copper Alloy T=0.30mm

Finish:

- Housing: Black
- Contact Pin: See P/N Option
- Shell: Gold Plated Over Nickel

Part No.: HDACM-40030-19 0 3 3

No. Of Pin 19

Packing 3:T&R(1000pcs)

Plating 3:Gold Plated On Contact Area,Sn Plated On Solder tails,Nickel Under Plated Over All

RoHS Compliant



		金上達科技股份有限公司 GOLDENSUNDA TECHNOLOGY CO.,LTD		TITLE: Mini HDMI 90° 19Pin SMT+DIP C Type									
				TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.		PART NO. HDACM-40030-19033		DWG NO. HDACM-400-C-01			
.x± 0.35	x.'± 2'	APR. C.F.Liao 20150511		UNITS: mm		CUSTOMER DRAWING							
.xx± 0.25	.x'± 1'	CHK. Abel 20150511		SIZE: A4						SCALE 4:1		SHEET 1 / 1	
.xxx± 0.15	.xx'± 0.5'	DRA. Michelle 20150511		SIZE: A4		SCALE 4:1		SHEET 1 / 1		REV A1		V	