



REV	MODIFICATION	DATE	DRAW
A0	Refer To MA20140103	2014.01.09	Michelle

RoHS Compliant

Specification

- 1.Current Rating:1.5A Max.
- 2.Voltage Rating:150V AC
- 3.Contact Resistance:30m Ω Max.
- 4.Insulation Resistance:500M Ω Min. At 500VDC/Minute
- 5.Dielectric Withstanding Voltage:1000VAC/Minute
- 6.Operating Temperature:-40 $^{\circ}$ C~+85 $^{\circ}$ C

Material:

- 1.Housing:Thermoplastic UL94V-0
- 2.Contact Pin:Copper Alloy T=0.35mm

Finish:

- 1.Housing:Black
- 2.Contact Pin:Gold Plated Over Nickel.

Part No.: RJ XX M - 1 0 0 0 1 - XX 0 1 5

AA:8P8C
AB:10P10C

Housing Material
1:PBT UL94V-0

Plating
5:Gold Plated 6u"
Over Nickel.

08:8C
10:10C

Packing
1:Tray



TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.	TITLE: RJ45 180° DIP			
.x \pm 0.35	x. \pm 2'	APR. Jefferson 20140109	PART NO. RJXXM-10001-XX015	DWG NO. RJAAM-100-C-01		
.xx \pm 0.25	.x \pm 1'	CHK. Abel 20140109	UNITS: mm	CUSTOMER DRAWING		
.xxx \pm 0.15	.xx \pm 0.5'	DRA. Michelle 20140109	SIZE: A4	SCALE Free	SHEET 1 / 1	
					REV A0 V	