



REV	MODIFICATION	DATE	DRAW
A0	Release To MA20130802	2013.08.06	Michelle
A1	Release To ECN20150404	2015.04.15	Michelle

Specification

- 1.Current Rating:1A
- 2.Voltage Rating:30V AC
- 3.Contact Resistance:30mΩ Max.
- 4.Insulation Resistance:1000MΩ Min. At 100V DC
- 5.Dielectric Withstanding Voltage:100VAC/Minute
- 6.Operating Temperature:-20°C~+85°C

Material:

- 1.Housing:High Temperature Thermoplastic UL94V-0
- 2.Contact Pin:Copper Alloy T=0.15mm
- 3.Shell:Copper Alloy T=0.25mm

Finish:

- 1.Housing:Black
- 2.Contact Pin:See P/N Option
- 3.Shell:Matte Tin Plated Over Nickel

Part No.: UBACM-41220-05 0 3 4

No. Of Pin: 05

Packing: 3:T&R (1500PCS/R)

4:Gold Flash On Contact Area. Sn Plated On Solder Tails Area.Nickel Under Plated



RoHS Compliant

		金上達科技股份有限公司 GOLDENSUNDA TECHNOLOGY CO.,LTD	
TOLERANCE UNLESS OTHERWISE SPECIFIED		TITLE: MICRO USB B FEMALE 90° 5P SMT	
.x± 0.35	x:± 2'	APR. C.F.Liao 20150415	PART NO. UBACM-41220-05034
.xx± 0.25	.x'± 1'	CHK. Abel 20150415	DWG NO. UBACM-412-C-01
.xxx± 0.15	.xx'± 0.5'	DRA. Michelle 20150415	UNITS: mm CUSTOMER DRAWING
		SIZE: A4	SCALE 5:1 SHEET 1 / 1 REV A1 V