



**RoHS Compliant**

REV	MODIFICATION	DATE	DRAW
A0	Release To MA20130912	2013.09.25	Seven

- Specification**
- 1.Current Rating:12A
  - 2.Voltage Rating:250V AC
  - 3.Insulation Resistance:1000MΩ Min At DC500V
  - 4.Dielectric Withstanding Voltage:2000VAC/Minute
  - 5.Operation Temperature:-55°C~+115°C

- Material:**
- 1.Housing:Thermoplastic UL94V-0
  - 2.Contact Pin:Copper Alloy SQ=1.0mm

- Finish:**
- 1.Housing:Green
  - 2.Contact Pin:Tin Plated Over Nickel.

Part No.: TBAAM-21001- XX 1 4 1  
 No. of Pin \_\_\_\_\_ Plating  
 02~24P \_\_\_\_\_  
 Packing \_\_\_\_\_ Over Nickel  
 4:Bag



**金上達科技股份有限公司**  
**GOLDENSUNDA TECHNOLOGY CO.,LTD**

**TOLERANCE UNLESS OTHERWISE SPECIFIED**

.x± 0.35	.x'± 2'	APR. Jay 20130925	TITLE: Terminal Block Male 5.08mm 90° DIP Pluggable Type	PART NO. TBAAM-21001-XX141	DWG NO. TBAAM-210-C-01
.xx± 0.25	.x'± 1'	CHK Michelle 20130925	UNITS: mm	<b>CUSTOMER DRAWING</b>	
.xxx± 0.15	.xx'± 0.5'	DRA Seven 20130925	SIZE: <b>A4</b>	SCALE 3:1	SHEET 1 / 1

REV A0 V