



REV	MODIFICATION	DATE	DRAW
A0	Release To MA20131008	2013.10.24	Michelle

RoHS Compliant

Specification

- Current Rating: 3A
- Voltage Rating: 60V AC/DC
- Insulation Resistance: 1000MΩ Min. At DC 100V
- Operating Temperature: -55°C ~ +125°C (For Gold Plated)
-40°C ~ +105°C (For Tin Plated)

Material:

- Housing: Thermoplastic UL94V-0
- Contact Pin: Copper Alloy Round Pin 0.51mm
- Clip: Copper Alloy

Finish:

- Housing: Black
- Contact Pin: Bright Tin Plated Over Nickel
- Clip: Gold Flash Over Nickel

Part No.: ISAAM-120 X 1-XX 1 2 3

1: Without Bar
2: With Bar

Plating
3: Gold Flash Over Ni.

Number Of Pin: 06~32
Packing: 2: Tube

	PIN	DIM.A	DIM.B		PIN	DIM.A	DIM.B
Without Bar	06	5.08	7.62	With Bar	18	20.32	22.86
	08	7.62	10.16		20	22.86	25.40
	10	10.16	12.70		22	25.40	27.94
	12	12.70	15.24		24	27.94	30.48
	14	15.24	17.78		28	33.02	35.56
	16	17.78	20.32	32	38.10	40.64	

發行
102.10.24
文管中心

金上達科技股份有限公司
GOLDENSUNDA TECHNOLOGY CO., LTD

TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.	TITLE: IC Socket 2.54mm 180° DIP Dual Row	
.x ± 0.35	x. ± 2'	APR. Jefferson 20131024	PART NO. ISAAM-120X1-XX123	DWG NO. ISAAM-120-C-01
.xx ± 0.25	.x' ± 1'	CHK. Abel 20131024	UNITS: mm	CUSTOMER DRAWING
.xxx ± 0.15	.xx' ± 0.5'	DRA. Michelle 20131024	SIZE: A4	SCALE Free

SHEET 1 / 1 REV A0 V