



REV	MODIFICATION	DATE	DRAW
A0	Release To Production	2010.09.21	Ivy
A1	Release To ECN20130609	2013.06.19	Michelle

#### Specification

- 1.Current Rating:3A
- 2.Contact Resistance:20mΩ Max.
- 3.Insulation Resistance:1000MΩ Min.
- 4.Dielectric Withstanding Voltage:500VAC/Minute
- 5.Operating Temperature:-25℃~+105℃

#### Material:

- 1.Housing: High Temperature Thermoplastic UL94V-0
- 2.Contact Pin:Copper Alloy SQ. Pin 0.64mm

#### Finish:

- 1.Housing:Black
- 2.Contact Pin:Gold Flash Over Nickel

Part No.:ED05400 XX 4 3 B P

Number of Pin  
06~50

Packing  
B:Bag

Housing Material  
4:NY6T UL94V-0 Black

Plating  
3:Gold Flash Over Nickel

PIN	DIM.A	DIM.B	DIM.C	PIN	DIM.A	DIM.B	DIM.C
06	5.08	12.94	15.24	26	30.48	38.34	40.64
08	7.62	15.48	17.78	30	35.56	43.42	45.72
10	10.16	18.02	20.32	32	38.10	45.96	48.26
12	12.70	20.56	22.86	34	40.64	48.50	50.80
14	15.24	23.10	25.40	40	48.26	56.12	58.42
16	17.78	25.64	27.94	44	53.34	61.20	63.50
20	22.86	30.72	33.02	50	60.96	68.82	71.12
24	27.94	35.80	38.10				



金上達科技股份有限公司

GOLDENSUNDA TECHNOLOGY CO.,LTD

TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.	TITLE: Box Header 2.54mm 180° H=8.80 DIP Dual Row	
.X± 0.35	.X'± 2'	APR. Jay 20130619	PART NO. ED05400XX43BP	DWG NO. ED05400XX43BP
.XX± 0.25	.X'± 1'	CHK. Seven 20130619	UNITS: mm CUSTOMER DRAWING	
.XXX± 0.15	.XX'± 0.5'	DRA. Michelle 20130619	SIZE: A4	SCALE 3:1
			SHEET 1 / 1	REV A1 V