



REV	MODIFICATION	DATE	DRAW
A0	Release To Production	2009.07.14	Abel
A1	下針尺寸修改	2010.06.15	AJ
A2	Release To ECN20130605	2013.06.10	Michelle

RoHS Compliant

- Specification
1. Current Rating: 3A AC/DC
 2. Voltage Rating: 25V AC/DC
 3. Contact Resistance: 20mΩ Max.
 4. Insulation Resistance: 5000MΩ Min. At DC 500V
 5. Dielectric Withstanding Voltage: 500 VAC/Minute
 6. Operating Temperature: -25°C ~ +85°C

- Material:
1. Housing: Thermoplastic UL94V-0
 2. Contact Pin: Copper Alloy T=0.40mm
- Finish:
1. Housing: Black
 2. Contact Pin: Gold Flash Over Nickel.

Part No.: ED05129 XX 8 3 Y F

Number Of Pin: 04~80

Packing: Y: Tray

Housing Material: 8: PBT UL94V-0 Black

Plating: 3: Gold Flash Over Nickel.



TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.	TITLE: Female Header 2.54mm 180° H=8.50 DIP Single Row			
.x± 0.35	x.± 2'	APR. Jay 20130610	PART NO. ED05129XX83YF		DWG NO. ED05129XX83YF	
.xx± 0.25	.x'± 1'	CHK. Seven 20130610	UNITS: mm		CUSTOMER DRAWING	
.xxx± 0.15	.xx'± 0.5'	DRA. Michelle 20130610	SIZE: A4	SCALE: 5:1	SHEET 1 / 1	REV A2 V