



P/N	DIM.A	DIM.B	DIM.C
ED03637XXXXCBF	7.20	3.20	1.50
ED03638XXXXCBF	8.70	3.20	3.00
ED03656XXXXCBF	11.60	6.10	3.00
ED03660XXXXCBF	15.00	8.70	3.80
ED036G2XXXXCBF	10.30	4.80	3.00

REV	MODIFICATION	DATE	DRAW
A0	Release To Production	2015.08.07	Michelle

RoHS Compliant

- Specification
- 1.Current Rating:3A
 - 2.Voltage Rating:25V AC
 - 3.Contact Resistance:20mΩ Max.
 - 4.Insulation Resistance:5000MΩ Min.
 - 5.Dielectric Withstanding Voltage:AC500V/Minute
 - 6.Operating Temperature:-25°C~+85°C

- Material:
- 1.Housing:High Temperature or Thermoplastic UL94V-0
 - 2.Contact Pin:Copper Alloy SQ. Pin 0.64mm

- Finish:
- 1.Housing:Black
 - 2.Contact Pin:Gold Plated

Part No.: ED036 XX XX X C B F
 See P/N Option—
 No. Of Pin 01~40
 Packing B:Bag
 Housing Material 4:HTN UL94V-0 Black H.F
 8:PBT UL94V-0 Black
 Plating C:Gold Plated



金上達科技股份有限公司
GOLDENSUNDA TECHNOLOGY CO.,LTD

TOLERANCE UNLESS OTHERWISE SPECIFIED	PROJ.	TITLE: Pin Header 2.54mm 180° H=2.50 DIP Single Row	
.x± 0.35	x.* 2'	APR. C.F.Liao 20150807	DWG NO. ED036XXXXXCBF
.xx± 0.25	.x.* 1'	CHK. Abel 20150807	CUSTOMER DRAWING
.xxx± 0.15	.xx.* 0.5'	DRA. Michelle 20150807	UNITS: mm
		SIZE: A4	SCALE 4:1
		SHEET 1 / 1	REV A0 V

RECOMMENDED P.C.B LAYOUT