

RoHS Compliant

REV	MODIFICATION	DATE	DRAW
A0	Release To Production	2010.01.28	AJ
A1	Release To ECN20130407	2013.05.09	Michelle
A2	Release To ECN20140305	2014.03.18	Michelle

Specification

- 1.Current Rating:1A
- 2.Voltage Rating:125V AC/DC
- 3.Contact Resistance:20mΩ Max.
- 4.Insulation Resistance:1000MΩ Min. At DC 500V
- 5.Dielectric Withstanding Voltage:AC500V/Minute
- 6.Operating Temperature:-40°C~+105°C

Material:

- △A2 1.Housing:High Temperature Thermoplastic UL94V-0 (H/F)
- 2.Contact Pin:Copper Alloy SQ. Pin 0.40mm

Finish:

- 1.Housing: Black
- △A2 2.Contact Pin:Gold Plated 0.60u" On Contact Area

Part No.: ED006XX XX 4 3 B F

No. Of Pin
06~100(=A0)

Packing
B:Bag

Housing Material

- △A2 4:HTN UL94V-0 Black (H/F)

Plating

- △A2 3:Gold Plated 0.60u" On Contact Area

P/N	DIM.A	DIM.B	DIM.C
ED00684XX43BF	9.00	4.00	3.00
ED00657XX43BF	7.30	3.00	2.30



金上達科技股份有限公司
GOLDENSUNDA TECHNOLOGY CO.,LTD

TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.	TITLE: Pin Header 1.27mm 180° H=2.00 DIP Dual Row	
.x± 0.35	x.'± 2'	APR. C.F. Liao 20140318	PART NO. ED006XXXX43BF	DWG NO. ED006XXXX43BF
.xx± 0.25	.x'± 1'	CHK. Abel 20140318	UNITS: mm CUSTOMER DRAWING	
.xxx± 0.15	.xx'± 0.5'	DRAW. Michelle 20140318	SIZE: A4	SCALE 6:1 SHEET 1 / 1 REV A2 V

