



REV	MODIFICATION	DATE	DRAW
A0	Release To FAI20110152	2011.02.21	Ivy
A1	Releas To ECN20130506	2013.05.29	Michelle

RoHS Compliant

Specification

- 1.Current Rating:1A AC/DC
- 2.Contact Resistance:20mΩ Max.
- 3.Insulation Resistance:5000MΩ Min.
- 4.Dielectric Withstanding Voltage:1000 VAC/Minute
- 5.Operating Temperature:-55°C~+105°C

Material:

- 1.Housing:High Temperature Thermoplastic UL94V-0
- 2.Contact Pin:Copper Alloy SQ. Pin 0.30mm
- 3.Cap:High Temperature Thermoplastic UL94V-0

Finish:

- 1.Housing:Black
- 2.Contact Pin:Gold Flash Over Nickel.
- 3.Cap:Black

Part No.: ES030B5 XX 4 3 0 P

Number Of Pin
04~20

Packing
0:T&R W/CAP

Housing Material
4:NY6T UL94V-0 Black

Plating
3:Gold Flash Over Nickel.

P/N	DIM.A	DIM.B	DIM.C
ES030B5XX430P	4.83	1.90	1.90



金上達科技股份有限公司
GOLDENSUNDA TECHNOLOGY CO.,LTD

TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.	TITLE: Pin Header 1.00mm 180° H=1.00 SMT Dual Row			
.x± 0.35	x.'± 2'	APR. Jay 20130529	PART NO. ES030B5XX430P		DWG NO. ES030B5XX430P	
.xx± 0.25	.x'± 1'	CHK. Seven 20130529	UNITS: mm	CUSTOMER DRAWING		
.xxx± 0.15	.xx'± 0.5'	DRA. Michelle 20130529	SIZE: A4	SCALE 6:1	SHEET 1 / 1	
			REV A1	V		