



REV	MODIFICATION	DATE	DRAW
A0	Release To ECN20140704	2014.07.14	Michelle

- Specification
- 1.Current Rating:0.5A
 - 2.Voltage Rating:50V AC/DC
 - 3.Contact Resistance:40mΩ Max.
 - 4.Insulation Resistance:100MΩ Min.
 - 5.Dielectric Withstanding Voltage:AC500V/Minute.
 - 6.Operating Temperature:-20℃~+105℃

- Material:
- 1.Housing:High Temperature Thermoplastic UL94V-0
 - 2.Contact Pin:Copper Alloy
 - 3.Cap: PI
- Finish:
- 1.Housing:Black
 - 2.Contact Pin:Gold Flash Over Nickel
 - 3.Cap: None

Part No.: ES09300 XX 9 3 X S

Number Of Pin 20~A0 (=100)

Packing T:Tube P:T&R With PI

Housing Material 9:NY9T UL94V-0 Black H/F

Plating 3:Gold Flash Over Nickel

RECOMMENDED P.C.B LAYOUT
(TOLERANCE±0.05)

RoHS Compliant



金上達科技股份有限公司
GOLDENSUNDA TECHNOLOGY CO.,LTD

TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.	TITLE: Board To Board Header 0.50mm H=2.74 SMT Dual Row	
.x± 0.35	x.± 2'	APR. C.F.Liao 20140714	PART NO. ES09300XX93XS	DWG NO. ES09300XX93XS
.xx± 0.25	.x'± 1'	CHK. Abel 20140714	UNITS: mm	CUSTOMER DRAWING
.xxx± 0.15	.xx'± 0.5'	DRA Michelle 20140714	SIZE: A4	SCALE 7:1
			SHEET 1 / 1	REV A0 V