

REV	MODIFICATION	DATE	DRAW
A1	Release To ECN20130307	2013.03.27	Seven
A2	Release To ECN20141108	2014.11.26	Michelle
A3	Release To ECN20150605	2015.06.09	Michelle



RoHS Compliant

- Specification**
- 1.Current Rating:7A AC/DC
 - 2.Voltage Rating:250V AC/DC
 - 3.Contact Resistance:10mΩ Max.
 - 4.Insulation Resistance:1000MΩ Min.
 - 5.Withstand Voltage:AC1500V/Minute
 - 6.Operating Temperature:-25°C~+85°C

Material:
1.Housing:Thermoplastic UL94V-2

Finish:
1.Housing:Natural

Use With:
1.Terminal:CC0050000B1AM


Part No.: BC00500 04 0 1 B 2

No. Of Pin
04

Packing
B:Bag (500pcs)

Housing Material
0:NY66 UL94V-2

Housing Color
1:Natural



金上達科技股份有限公司

GOLDENSUND TECHNOLOGY CO.,LTD

TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.	TITLE: Wire To Board & Wire Housing 5.08mm Male Single Row		
.x± 0.35	x.'± 2'	APR. C.F.Liao 20150609	PART NO. BC005000401B2	DWG NO. BC005000401B2	
.xx± 0.25	.x'± 1'	CHK: Abel 20150609	UNITS: mm	CUSTOMER DRAWING	
.xxx± 0.15	.xx'± 0.5'	DRA: Michelle 20150609	SIZE: A4	SCALE 3:1	SHEET 1 / 1
			REV A3	V	