



A2

RoHS Compliant

REV	MODIFICATION	DATE	DRAW
A0	Release To Production	2008.08.25	Ricky
A1	Release To Modify A4 DWG	2009.08.20	AJ
A2	Release To ECN20130308	2013.03.25	Seven

Specification

- 1.Current Rating:1A AC/DC
- 2.Voltage Rating:50V AC/DC
- 3.Contact Resistance:20mΩ Max.
- 4.Insulation Resistance:100MΩ Min.
- 5.Withstand Voltage:500V AC/Minute
- 6.Operating Temperature:-25°C~+85°C

Material:

1.Housing:Thermoplastic UL94V-0

Finish:

1.Housing:White

Part No.: BC08700 XX 7 1 B E

Number of Pin 20~50
Packing B:Bag

Housing Material 7:PBT UL94V-0

Housing Color 1:White

Pin	DIM.A	DIM.B	DIM.C	DIM.D
20	13.0	9.0	11.2	10.37
30	18.0	14.0	16.2	15.37
40	23.0	19.0	21.2	20.37
50	28.0	24.0	26.2	25.37

金上達科技股份有限公司
GOLDENSUNDA TECHNOLOGY CO.,LTD

TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.	TITLE: Wire To Board Housing 1.00mm Dual Row 20~50P	
.x± 0.35	.x'± 2'	APR. Jay 20130325	PART NO. BC08700XX71BE	DWG NO. BC08700XX71BE
.xx± 0.25	.x'± 1'	CHK. Michelle 20130325	UNITS: mm	CUSTOMER DRAWING
.xxx± 0.15	.xx'± 0.5'	DRA. Seven 20130325	SIZE: A4	
		SCALE 5:1	SHEET 1 / 1	REV A2