



REV	MODIFICATION	DATE	DRAW
A0	Release To Product	2010.01.15	AJ
A1	Release To ECN20130308	2013.03.25	Seven
A2	Release To ECN20140103	2014.01.14	Michelle

RoHS Compliant

Specification

1. Current Rating: 1A AC/DC
2. Voltage Rating: 250V AC/DC
3. Contact Resistance: 20mΩ Max.
4. Insulation Resistance: 1000MΩ Min. At DC 500V
5. Withstand Voltage: 800V AC/Minute
6. Operating Temperature: -25°C ~ +85°C

Material:

1. Housing: Temperature Thermoplastic UL94V-2

Finish:

1. Housing: Black

Part No.: BCA1100 XX 0 3 B 8

Number Of Pin: 04~80
 Packing: B: Bag
 Housing Material: 0: NY66 UL94V-2 Black

Pin	DIM.A	DIM.B	Pin	DIM.A	DIM.B
2x2	2.00	4.20	2x15	28.00	30.20
2x3	4.00	6.20	2x16	30.00	32.20
2x4	6.00	8.20	2x17	32.00	34.20
2x5	8.00	10.20	2x18	34.00	36.20
2x6	10.00	12.20	2x19	36.00	38.20
2x7	12.00	14.20	2x20	38.00	40.20
2x8	14.00	16.20	2x21	40.00	42.20
2x9	16.00	18.20	2x22	42.00	44.20
2x10	18.00	20.20	2x23	44.00	46.20
2x11	20.00	22.20	2x24	46.00	48.20
2x12	22.00	24.20	2x25	48.00	50.20
2x13	24.00	26.20	2x30	58.00	60.20
2x14	26.00	28.20	2x40	78.00	80.20



金上達科技股份有限公司
GOLDENSUNDA TECHNOLOGY CO., LTD

TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJ.	TITLE: Wire To Board Housing 2.00mm Dual Row	
.x ± 0.35	x. ± 2'	APR. Jefferson 20140114	PART NO. BCA1100XX03B8	DWG NO. BCA1100XX03B8
.xx ± 0.25	.x' ± 1'	CHK. Abel 20140114	UNITS: mm	CUSTOMER DRAWING
.xxx ± 0.15	.xx' ± 0.5'	DRA. Michelle 20140114	SIZE: A4	SCALE 6:1
			SHEET 1 / 1	REV A2