

RoHS Compliant

REV	MODIFICATION	DATE	DRAW
A2	Release To ECN20130303	2013.03.12	Seven
A3	Release To ECN20131004	2013.10.09	Michelle
A4	Release To ECN20150610	2015.06.23	Michelle

Specification

- 1.Current Rating:3A AC/DC
- 2.Voltage Rating:250V AC/DC
- 3.Contact Resistance:10mΩ Max.
- 4.Insulation Resistance:1000MΩ Min. At DC 500V
- 5.Dielectric Withstanding Voltage:AC 800V/Minute
- 6.Operating Temperature:-25°C~+85°C

Material:

- 1.Housing:High Temperature Thermoplastic UL94V-0
- 2.Contact Pin:Copper Alloy SQ. Pin 0.64mm

Finish:

- 1.Housing:Natural
- 2.Contact Pin:Bright Tin Plated Over Nickel

Part No.: ADO4801 XX 1 4 5 2

△ No. Of Pin
02~10

Packing
5:Bag

Housing Material
1:PA66 UL94V-0 Natural

Plating
4:Bright Tin Plated
Over Nickel With Kink

PIN	DIM.A	DIM.B	PIN	DIM.A	DIM.B
02	2.50	7.50	07	15.00	20.00
03	5.00	10.00	08	17.50	22.50
04	7.50	12.50	09	20.00	25.00
05	10.00	15.00	10	22.50	27.50
06	12.50	17.50			



△ RECOMMENDED P.C.B LAYOUT

		金上達科技股份有限公司 GOLDENSUNDA TECHNOLOGY CO.,LTD			
		TITLE: Wire To Board Wafer 2.50mm 90° DIP Single Row			
TOLERANCE UNLESS OTHERWISE SPECIFIED	PROJ.	APR. C.F.Liao 20150623		PART NO. ADO4801XX1452	
.x± 0.35	x.± 2'	CHK. Abel 20150623		DWG NO. ADO4801XX1452	
.xx± 0.25	.x'± 1'	DRA. Michelle 20150623		CUSTOMER DRAWING	
.xxx± 0.15	.xx'± 0.5'	SIZE: A4	SCALE 4:1	SHEET 1 / 1	REV A4 V