



RoHS Compliant

發行
103.10.31
文管中心

| REV | MODIFICATION | DATE | DRAW |
|-----|------------------------|------------|----------|
| A0 | Release To Product | 2010.01.20 | Abel |
| A1 | Release To ECN20130307 | 2013.03.27 | Seven |
| A2 | Release To ECN20141006 | 2014.10.31 | Michelle |

Specification
 1.Current Rating:7A AC/DC
 2.Voltage Rating:250V AC/DC
 3.Contact Resistance:10mΩ Max.
 4.Insulation Resistance:1000MΩ Min. At DC 500V
 5.Withstand Voltage:AC1500V/Minute
 6.Operating Temperature:-25°C~+85°C

Material:
 1.Housing:Thermoplastic UL94V-2
 Finish:
 1.Housing:Nature
 Part No.:BC00109 XX 0 1 5 2

Number of Pin
 A2 02~10
 Packing
 5:Bag

Housing Material
 0:NY66 UL94V-2
 Housing Color
 1:Nature

| PIN | DIM.A | DIM.B | PIN | DIM.A | DIM.B |
|-----|-------|-------|-----|-------|-------|
| 02 | 5.08 | 10.16 | 07 | 30.48 | 35.56 |
| 03 | 10.16 | 15.24 | 08 | 35.56 | 40.64 |
| 04 | 15.24 | 20.32 | 09 | 40.64 | 45.72 |
| 05 | 20.32 | 25.40 | 10 | 45.72 | 50.80 |
| 06 | 25.40 | 30.48 | | | |

金上達科技股份有限公司
GOLDENSUNDA TECHNOLOGY CO.,LTD

| | | | | | |
|--------------------------------------|-------------|---------------------------|--|--------------------------|-------------|
| TOLERANCE UNLESS OTHERWISE SPECIFIED | | PROJ. | TITLE: Wire To Board Housing 5.08mm Single Row | | |
| .x± 0.35 | x.*± 2' | APR. C.F.Liao 20141031 | PART NO. BC00109XX0152 | DWG NO. BC00109XX0152 | |
| .xx± 0.25 | .x.*± 1' | CHK. Abel 20141031 | UNITS: mm | CUSTOMER DRAWING | |
| .xxx± 0.15 | .xx.*± 0.5' | DRA. Michelle 20141031 | SIZE: A4 | SCALE 3:1 | SHEET 1 / 1 |
| | | | | REV A2 | V |